
# Outline Level S


OUT 065 227 052A 8030 10 99 OP 40 LV

Recessed Linear Luminary




| | |
|---|---|
| **Luminaire Group** | Linear |
| **Mounting Type** | Recessed |
| **Luminary Color** | RAL 9010 - RAL 9005 |
| **Housing** | Aluminum extruded profile |
| **Optics** | Opal Diffuser |
| **Light Source** | LED |
| **Electrical Protection Class** | CLASS II |
| **Operating Temperature** | -20°C / +40°C |
| **Luminous Flux** | 4640 |
| **Consumption Power** | 52 |
| **Luminaire Efficiency** | 92,81 lm/W |
| **Color Rendering (CRI)** | >80 |
| **Light Color Temperature (CCT)** | 2700K/3000K/4000K/6500K |
| **Color Tolerance** | < 3 SDCM |
| **Driver Type** | On/Off |
| **Driver Brand** | Tridonic |
| **LED Brand** | Samsung |
| **Input Voltage / Frequency** | 220-240 V AC 50/60 Hz |
| **Power Factor** | >0.9 |
| **Surge** | 1kV |
| **THD (AKIM)** | >%20 |
| **LED life** | >70.000 hours |

## Technical Drawing




## Photometric Curve



| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|---|---|---|---|---|---|---|---|
| | OUT 065 227 052A 8030 10 99 OP 40 LV | 52 | 4640 | >80 | 4000 | 120° Opal Diffuser | 2270x65x67 |