

Loopy



LPY 008 011 009B 8040 10 15 SD 20 00



Recessed Concept Ceiling Luminary



| | |
|--------------------------------------|--|
| Luminaire Group | Concept Ceiling |
| Mounting Type | Recessed |
| Luminaire Color | RAL 9005 - RAL 9010 - RAL 9006 |
| Housing | Aluminum DKP Sheet |
| Optics | Reflector |
| Electrical Protection Class | CLASS II |
| Operating Temperature | -20°C / +40°C |
| Luminous Flux | 810 |
| Consumption Power | 9 |
| Luminaire Efficiency | 90 lm/W |
| Color Rendering (CRI) | >80 |
| Light Color Temperature (CCT) | 2700K/3000K/4000K/6500K |
| Color Tolerance | < 3 SDCM |
| Driver Type | On/Off |
| Driver Brand | Tridonic |
| LED Brand | Samsung |
| Input Voltage / Frequency | 220-240 V AC 50/60 Hz |
| Power Factor | >0.9 |
| Surge | 1kV |
| THD (AKIM) | >%20 |
| LED life | >100.000 hours |
| Option | On-Off / Dali / 1-10V / With Emergency Kit |



| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|---------------|-----------------|
| | LPY 008 011 009B 8040 10 15 SD 20 00 | 9 | 810 | >80 | 4000 | 15° Reflector | Ø87x113 |