

Rainbow Deep



RNB 010 015 007A 9040 10 15 SD 44 DP



Recessed Downlight & Spot Luminary



| | |
|--------------------------------------|--|
| Luminaire Group | Downlight & Spot |
| Mounting Type | Recessed |
| Luminaire Color | RAL 9010 - RAL 9005 - RAL 9006 - RAL 9016 |
| Housing | Aluminum Extrusion |
| Optics | 15° 30° 40° Reflector & Transparent Diffuser |
| Light Source | LED |
| Electrical Protection Class | CLASS II |
| IP | 44 |
| IK | 03 |
| Operating Temperature | -20°C / +40°C |
| Luminous Flux | 511 |
| Consumption Power | 7 |
| Luminaire Efficiency | 73 lm/W |
| Color Rendering (CRI) | >80 |
| Light Color Temperature (CCT) | 2700K/3000K/4000K/6500K |
| Color Tolerance | < 3 SDCM |
| Driver Type | On/Off |
| Driver Brand | Tridonic |
| LED Brand | Samsung |
| Input Voltage / Frequency | 220-240 V AC 50/60 Hz |
| Power Factor | >0.9 |
| Surge | 1kV |
| THD (AKIM) | >%20 |
| LED life | >102.000 hours |
| Option | On-Off / Dali / 1-10V / With Emergency Kit |



| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|---------------|-----------------|
| | RNB 010 015 007A 9040 10 15 SD 44 DP | 7 | 511 | >80 | 4000 | 15° Reflector | Ø110 |