Orbita


RNB 010 010 026A 8040 10 40 SD 44 00 OB

Pendant Acoustic Solutions Luminary




Luminaire Group	Acoustic Solutions
Mounting Type	Pendant
Luminary Color	RAL 9006 - RAL 9005 - RAL 9010
Housing	Aluminum Injection & Acoustic Panel
Optics	19° 30° 55° Reflector & Transparent Diffuser
Light Source	LED
Electrical Protection Class	CLASS II
IP	20
IK	02
Operating Temperature	-20°C / +40°C
Luminous Flux	2080
Consumption Power	26
Luminaire Efficiency	80 lm/W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	2700K/3000K/4000K/6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Driver Brand	Tridonic
LED Brand	Samsung
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	>70.000 hours
Option	On-Off / Dali / 1-10V / With Emergency Kit

Technical Drawing



Photometric Curve



SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
	RNB 010 010 026A 8040 10 40 SD 44 00 OB	26	2080	>80	4000	40° Reflector	Ø100x95