

# Margarita S

MAR 011 009 019K 8030 10 90 LN 65 00




Floor Facade & Landscape Luminary




|                                      |                         |
|--------------------------------------|-------------------------|
| <b>Luminaire Group</b>               | Facade & Landscape      |
| <b>Mounting Type</b>                 | Floor                   |
| <b>Luminary Color</b>                | RAL 9005 - RAL 9016     |
| <b>Housing</b>                       | Aluminum Extrusion      |
| <b>Optics</b>                        | 15° 40° 90° Lens        |
| <b>Light Source</b>                  | LED                     |
| <b>Electrical Protection Class</b>   | CLASS II                |
| <b>IP</b>                            | 65                      |
| <b>IK</b>                            | 08                      |
| <b>Operating Temperature</b>         | -20°C / +40°C           |
| <b>Luminous Flux</b>                 | 1520                    |
| <b>Consumption Power</b>             | 19                      |
| <b>Luminaire Efficiency</b>          | 80 lm/W                 |
| <b>Color Rendering (CRI)</b>         | >80                     |
| <b>Light Color Temperature (CCT)</b> | 2700K/3000K/4000K/6500K |
| <b>Color Tolerance</b>               | < 3 SDCM                |
| <b>Driver Type</b>                   | On/Off                  |
| <b>Input Voltage / Frequency</b>     | 220-240 V AC 50/60 Hz   |
| <b>Power Factor</b>                  | >0.9                    |
| <b>Surge</b>                         | 1kV                     |
| <b>THD (AKIM)</b>                    | >%20                    |
| <b>LED life</b>                      | >70.000 hours           |

Technical Drawing



Photometric Curve



| SKU | Product Code                         | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics   | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|----------|-----------------|
|     | MAR 011 009 019K 8030 10 90 LN 65 00 | 19        | 1520               | >80 | 4000    | 90° Lens | Ø119            |

[www.atellighting.com](http://www.atellighting.com)