

Orii

ORI 020 020 005Y 8030 10 99 OP 65 00




Concrete Park & Garden Luminary



Luminaire Group	Park & Garden
Mounting Type	Concrete
Housing	Dkp Sheet
Optics	Acrylic Diffuser
Light Source	LED
Electrical Protection Class	CLASS II
IP	65
IK	02
Operating Temperature	-20°C / +40°C
Luminous Flux	290
Consumption Power	5
Luminaire Efficiency	58 lm/W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	2700K/3000K/4000K/6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Driver Brand	Tridonic
LED Brand	Samsung
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	>70.000 hours
Option	On-Off / Dali / 1-10V

Technical Drawing



SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
74000081□	ORI 020 020 005Y 8030 10 99 OP 65 00	5	290	>80	4000	360° Opal Diffuser	200x200x200

www.atellighting.com