Trio


TRİ 2000 2000 030M 8040 10 30 AS 66 00

Concrete Park & Garden Luminary




Luminaire Group	Park & Garden
Mounting Type	Concrete
Luminary Color	RAL 9006 - RAL 9005 - RAL 9010
Housing	AlAluminum Extrusion
Optics	Reflector
Light Source	LED
Electrical Protection Class	CLASS II
IP	66
IK	08
Operating Temperature	-20°C / +40°C
Luminous Flux	4200
Consumption Power	30
Luminaire Efficiency	140 lm/W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	2700K/3000K/4000K/6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Driver Brand	Tridonic
LED Brand	Samsung
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	>70.000 hours
Option	On-Off / Dali / 1-10V

Technical Drawing



Photometric Curve



SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
	TRİ 2000 2000 030M 8040 10 30 AS 66 00	30	4200	>80	4000	AS° Reflector	2000