

Tubline

TUB 002 100 0012S 8040 10 99 OP 65 00




Surface Mounted Facade & Landscape Luminary



| | |
|--------------------------------------|-------------------------------|
| Luminaire Group | Facade & Landscape |
| Mounting Type | Surface Mounted |
| Housing | Polycarbonate |
| Optics | Polycarbonate Acrylic |
| Light Source | LED |
| Electrical Protection Class | CLASS II |
| IP | 65 |
| IK | 02 |
| Operating Temperature | -20°C / +40°C |
| Luminous Flux | 869 |
| Consumption Power | 12 |
| Luminaire Efficiency | 69 lm/W |
| Color Rendering (CRI) | >80 |
| Light Color Temperature (CCT) | 2700K / 3000K / 4000K / 6500K |
| Color Tolerance | < 3 SDCM |
| Driver Type | On/Off |
| Driver Brand | Tridonic |
| LED Brand | Samsung |
| Input Voltage / Frequency | 220-240 V AC 50/60 Hz |
| Power Factor | >0.9 |
| Surge | 1kV |
| THD (AKIM) | >%20 |
| LED life | >70.000 hours |
| Option | On-Off / Dali / 1-10V |

Technical Drawing



| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|-----|---------------------------------------|-----------|--------------------|-----|---------|-------------------------------|-------------------|
| | TUB 002 100 0012S 8040 10 99 OP 65 00 | 12 | 869 | >80 | 4000 | 180° Polycarbonate Acrylic | Ø30mm L:1000□□ |

www.atellighting.com