

Stair



STI 027 078 012S 8040 16 99 OP 54 00 (3 Hour kit with Sensor)



Surface Mounted Surface Mounted Luminary



| | |
|--------------------------------------|--|
| Luminaire Group | Surface Mounted |
| Mounting Type | Surface Mounted |
| Luminaire Color | RAL 9016 |
| Housing | Thermoplastic PC |
| Optics | Opal PMMA |
| Light Source | LED |
| Electrical Protection Class | CLASS II |
| IP | 54 |
| IK | 02 |
| Operating Temperature | -15°C / +45°C |
| Luminous Flux | 1080 |
| Consumption Power | 12 |
| Luminaire Efficiency | 90 lm/W |
| Color Rendering (CRI) | >80 |
| Light Color Temperature (CCT) | 2700K/3000K/4000K/6500K |
| Color Tolerance | < 3 SDCM |
| Driver Type | On/Off |
| Driver Brand | Tridonic |
| LED Brand | Samsung |
| Input Voltage / Frequency | 220-240 V AC 50/60 Hz |
| Power Factor | >0.9 |
| Surge | 1kV |
| THD (AKIM) | >%20 |
| LED life | 70.000 hours |
| Option | On-Off / Dali / 1-10V / With Emergency Kit / Sensor |



| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|-----|--|-----------|--------------------|-----|---------|-------------------|-----------------|
| | STI 027 078 012S 8040 16 99 OP 54 00 (3 Hour kit with Sensor) | 12 | 1080 | >80 | 4000 | 180° Opal PMMA | 270X78 |