

# Stair



STI 027 078 026S 8040 13 99 OP 54 00 (3 Hours with Lock)



Surface Mounted Surface Mounted Luminaire



|                                      |   |
|--------------------------------------|---|
| <b>Luminaire Group</b>               | Surface Mounted                                     |
| <b>Mounting Type</b>                 | Surface Mounted                                     |
| <b>Luminaire Color</b>               | RAL 9016  |
| <b>Housing</b>                       | Thermoplastic PC                                    |
| <b>Optics</b>                        | Opal PMMA   |
| <b>Light Source</b>                  | LED   |
| <b>Electrical Protection Class</b>   | CLASS II  |
| <b>IP</b>                            | 54  |
| <b>IK</b>                            | 02  |
| <b>Operating Temperature</b>         | -15°C / +45°C                                       |
| <b>Luminous Flux</b>                 | 2340  |
| <b>Consumption Power</b>             | 26  |
| <b>Luminaire Efficiency</b>          | 90 lm/W   |
| <b>Color Rendering (CRI)</b>         | >80   |
| <b>Light Color Temperature (CCT)</b> | 2700K/3000K/4000K/6500K                             |
| <b>Color Tolerance</b>               | < 3 SDCM  |
| <b>Driver Type</b>                   | On/Off  |
| <b>Driver Brand</b>                  | Tridonic  |
| <b>LED Brand</b>                     | Samsung   |
| <b>Input Voltage / Frequency</b>     | 220-240 V AC 50/60 Hz                               |
| <b>Power Factor</b>                  | >0.9  |
| <b>Surge</b>                         | 1kV   |
| <b>THD (AKIM)</b>                    | >%20  |
| <b>LED life</b>                      | 70.000 hours  |
| <b>Option</b>                        | On-Off / Dali / 1-10V / With Emergency Kit / Sensor |



| SKU | Product Code  | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics         | Dimensions (mm) |
|-----|---|-----------|--------------------|-----|---------|----------------|-----------------|
|     | STI 027 078 026S 8040 13 99 OP 54 00<br>(3 Hours with Lock) | 26        | 2340               | >80 | 4000    | 180° Opal PMMA | 270X78          |