Around


ARD 032 010 180S 8040 10 90 LN 65 00

Surface Mounted Industrial Luminary




Luminaire Group	Industrial
Mounting Type	Surface Mounted
Luminary Color	RAL 9005
Housing	Electrostatic Powder Coated Aluminum Extrusion Body
Optics	60° / 90° Pc Lens
Light Source	LED
Electrical Protection Class	CLASS II
IP	65
IK	08
Operating Temperature	-20°C / +40°C
Luminous Flux	27010
Consumption Power	180
Luminaire Efficiency	157 lm/W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	2700K / 3000K / 4000K / 6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Driver Brand	Philips
LED Brand	Samsung
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	4kV
THD (AKIM)	>%20
LED life	>100.000 hours
Option	On-Off / Dali / 1-10V / With Emergency Kit / Industrial

Technical Drawing



Photometric Curve



SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
	ARD 032 010 180S 8040 10 90 LN 65 00	180	27010	>80	4000	90° Pc Lens	Ø320x108