

Via

VIA 006 023 007D 8040 10 40 CA 65 00




Surface Mounted Wall Mount Luminaire




| | |
|--------------------------------------|-------------------------|
| Luminaire Group | Wall Mount |
| Mounting Type | Surface Mounted |
| Housing | DKP Sheet |
| Optics | Reflector & Glass |
| Light Source | LED |
| Electrical Protection Class | CLASS II |
| IP | 65 |
| Operating Temperature | -20°C / +40°C |
| Luminous Flux | 630 |
| Consumption Power | 7 |
| Luminaire Efficiency | 90 lm/W |
| Color Rendering (CRI) | >80 |
| Light Color Temperature (CCT) | 2700K/3000K/4000K/6500K |
| Color Tolerance | < 3 SDCM |
| Driver Type | On/Off |
| Driver Brand | Tridonic |
| LED Brand | Samsung |
| Input Voltage / Frequency | 220-240 V AC 50/60 Hz |
| Power Factor | >0.9 |
| Surge | 1kV |
| THD (AKIM) | >%20 |
| LED life | >70.000 hours |
| Option | On-Off / Dali / 1-10V |

Technical Drawing



Photometric Curve



| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|---------------|-----------------|
| | VIA 006 023 007D 8040 10 40 CA 65 00 | 7 | 630 | >80 | 4000 | 40° Reflector | Ø60x230mm |

www.atellighting.com

20.06.2026 - To access up-to-date information and data about the product, visit the product page: [Via](#)