Protector


PRD 036 042 200Y 8030 10 SM LN 66 00

Pole Mounted Road Lighting & Floodlight Luminary




Luminaire Group	Road Lighting & Floodlight
Mounting Type	Pole Mounted
Luminary Color	RAL 9005
Housing	Electrostatic Powder Coated Aluminium
Optics	4 mm Tempered Glass
Light Source	Mid Power LED
Electrical Protection Class	CLASS II
IP	66
IK	08
Operating Temperature	-20°C / +40°C
Luminous Flux	26000
Consumption Power	200
Luminaire Efficiency	130 lm/W
Color Rendering (CRI)	70
Light Color Temperature (CCT)	3000
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	>100.000 hours
Option	SPD, IP68 Connector

Technical Drawing



Photometric Curve



SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
	PRD 036 042 200Y 8030 10 SM LN 66 00	200	26000	70	3000	Symmetrical Lens	421x360x62