
ShoreRec S


Surface Mounted Linear Luminary




Luminaire Group	Linear
Mounting Type	Surface Mounted
Luminary Color	RAL 9010 - RAL 9005
Housing	Aluminum extruded profile
Optics	Opal Diffuser
Light Source	LED
Electrical Protection Class	CLASS II
IP	40
IK	03
Operating Temperature	-20°C / +40°C
Luminous Flux	11232 lm / 14976 lm / 18720 lm / 22464 lm
Consumption Power	104 W / 130 W / 156 W / 78 W
Luminaire Efficiency	144 lm/W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	2700K/3000K/4000K/6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Driver Brand	Tridonic
LED Brand	Samsung
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	>70.000 hours
Option	On-Off / Dali / 1-10V / With Emergency Kit

Technical Drawing







Photometric Curve




ShoreRec S

Surface Mounted Linear Luminary





Photometric Curve



SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
	SRC 117 061 078S 8040 10 99 OP 40 00	78	11232	>80	4000	120° Opal Diffuser	610x1170x47 x70
	SRC 145 089 104S 8040 10 99 OP 40 00	104	14976	>80	4000	120° Opal Diffuser	890x1450x47 x70mm□□
	SRC 173 117 130S 8040 10 99 OP 40 00	130	18720	>80	4000	120° Opal Diffuser	1170x1730x4 7x70
	SRC 201 145 156S 8040 10 99 OP 40 00	156	22464	>80	4000	120° Opal Diffuser	1450x2010x4 7x70