

T24 MainGrid




Recessed Concept Ceiling Luminary




| | |
|--------------------------------------|---|
| Luminaire Group | Concept Ceiling |
| Mounting Type | Recessed |
| Luminaire Color | RAL 9005 - RAL 9010 |
| Housing | Aluminum extruded profile |
| Optics | Opal Diffuser |
| Electrical Protection Class | CLASS II |
| Operating Temperature | -20°C / +40°C |
| Luminous Flux | 1350 lm / 2700 lm |
| Consumption Power | 13 W / 26 W |
| Luminaire Efficiency | 103,8 lm/W |
| Color Rendering (CRI) | >80 |
| Light Color Temperature (CCT) | 2700K/3000K/4000K/6500K |
| Color Tolerance | < 3 SDCM |
| Driver Type | On/Off |
| Driver Brand | Tridonic |
| LED Brand | Samsung |
| Input Voltage / Frequency | 220-240 V AC 50/60 Hz |
| Power Factor | >0.9 |
| Surge | 1kV |
| THD (AKIM) | >%20 |
| LED life | >70.000 hours |
| Option | On-Off / Dali / 1-10V / With Emergency Kit |

Technical Drawing



Photometric Curve



| SKU | Product Code | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|--------------------|-----------------|
| | MGD 024 117 026A 8040 10 99 OP 40 00 | 26 | 2700 | >80 | 4000 | 120° Opal Diffuser | 575x12x24 |
| | MGD 024 057 013A 8040 10 99 OP 40 00 | 13 | 1350 | >80 | 4000 | 120° Opal Diffuser | 1175x12x24 |