
Ozzo Trimless

Recessed Downlight & Spot Luminary




Luminaire Group	Downlight & Spot
Mounting Type	Recessed
Luminary Color	RAL 9005 - RAL 9006 - RAL 9010
Housing	DKP Sheet
Optics	15° 30° 40° Reflector & Opal Diffuser
Light Source	LED
Electrical Protection Class	CLASS II
IP	44
IK	02
Operating Temperature	-20°C / +40°C
Luminous Flux	1170 lm / 630 lm / 890 lm
Consumption Power	13 W / 7 W / 9 W
Luminaire Efficiency	90 lm/W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	2700K/3000K/4000K/6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Driver Brand	Tridonic
LED Brand	Samsung
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	>70.000 hours
Option	On-Off / Dali / 1-10V / With Emergency Kit

Technical Drawing



Photometric Curve




www.atellighting.com

Ozzo Trimless

Recessed Downlight & Spot Luminary

Technical Drawing





SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
13500013□	OZZ 009 009 007T 8040 10 15 SD 40 00	7	630	>80	4000	15° Reflector	93x93x98
13500031□	OZZ 009 009 007T 8040 10 30 SD 40 00	7	630	>80	4000	30° Reflector	93x93x98
13500049	OZZ 009 009 007T 8040 10 40 SD 40 00	7	630	>80	4000	40° Reflector	93x93x98
13500067	OZZ 009 009 009T 8040 10 15 SD 40 00	9	890	>80	4000	15° Reflector	93x93x98
13500085	OZZ 009 009 009T 8040 10 30 SD 40 00	9	890	>80	4000	30° Reflector	93x93x98
13500103	OZZ 009 009 009T 8040 10 40 SD 40 00	9	890	>80	4000	40° Reflector	93x93x98
13500121	OZZ 009 009 013T 8040 10 15 SD 40 00	13	1170	>80	4000	15° Reflector	93x93x98
13500139	OZZ 009 009 013T 8040 10 30 SD 40 00	13	1170	>80	4000	30° Reflector	93x93x98
13500157	OZZ 009 009 013T 8040 10 40 SD 40 00	13	1170	>80	4000	40° Reflector	93x93x98