
Dimple Drums


Surface Mounted Surface Mounted Luminary




Luminaire Group	Surface Mounted
Mounting Type	Surface Mounted
Luminary Color	RAL 9006 - RAL 9005 - RAL 9010
Housing	DKP Sheet
Optics	Opal Diffuser
Light Source	LED
Electrical Protection Class	CLASS II
IP	40
IK	02
Operating Temperature	-20°C / +40°C
Luminous Flux	11750 lm / 4730 lm / 6290 lm
Consumption Power	109 W / 35 W / 48 W
Luminaire Efficiency	135 lm/W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	2700K/3000K/4000K/6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Driver Brand	Tridonic
LED Brand	Samsung
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	70.000 hours
Option	On-Off / Dali / 1-10V / With Emergency Kit

Technical Drawing






Photometric Curve





www.atellighting.com


Dimple Drums

Surface Mounted Surface Mounted Luminary










Photometric Curve



SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
	DDR 040 025 035S 9040 10 99 OP 40 00	35	4730	>80	4000	120° Diffuser	Ø450x250
	DDR 060 025 048S 9040 10 99 OP 40 00	48	6290	>80	4000	120° Diffuser	Ø650x250

Dimple Drums

Surface Mounted Surface Mounted Luminary

SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
	DDR 090 025 109S 9040 10 99 OP 40 00	109	11750	>80	4000	120° Diffuser	Ø910x250