

# Dimple Drums End





Surface Mounted Surface Mounted Luminary




|                                      |  |
|--------------------------------------|--|
| <b>Luminaire Group</b>               | Surface Mounted                            |
| <b>Mounting Type</b>                 | Surface Mounted                            |
| <b>Luminaire Color</b>               | RAL 9006 - RAL 9005 - RAL 9010             |
| <b>Housing</b>                       | DKP Sheet                                  |
| <b>Optics</b>                        | Opal Diffuser                              |
| <b>Light Source</b>                  | LED  |
| <b>Electrical Protection Class</b>   | CLASS II                                   |
| <b>IP</b>                            | 40   |
| <b>IK</b>                            | 02   |
| <b>Operating Temperature</b>         | -20°C / +40°C                              |
| <b>Luminous Flux</b>                 | 19575 lm / 6210 lm / 8640 lm               |
| <b>Consumption Power</b>             | 145 W / 46 W / 65 W                        |
| <b>Luminaire Efficiency</b>          | 135 lm/W                                   |
| <b>Color Rendering (CRI)</b>         | >80  |
| <b>Light Color Temperature (CCT)</b> | 2700K/3000K/4000K/6500K                    |
| <b>Color Tolerance</b>               | < 3 SDCM                                   |
| <b>Driver Type</b>                   | On/Off                                     |
| <b>Driver Brand</b>                  | Tridonic                                   |
| <b>LED Brand</b>                     | Samsung                                    |
| <b>Input Voltage / Frequency</b>     | 220-240 V AC 50/60 Hz                      |
| <b>Power Factor</b>                  | >0.9                                       |
| <b>Surge</b>                         | 1kV  |
| <b>THD (AKIM)</b>                    | >%20                                       |
| <b>LED life</b>                      | 70.000 hours                               |
| <b>Option</b>                        | On-Off / Dali / 1-10V / With Emergency Kit |

Technical Drawing





Photometric Curve



# Dimple Drums End



Surface Mounted Surface Mounted Luminary



| SKU | Product Code                             | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics        | Dimensions (mm) |
|-----|--|-----------|--------------------|-----|---------|---------------|-----------------|
|     | DDR 040 025 046S 9040 10 99 OP 40 00 END | 46        | 6210               | >80 | 4000    | 120° Diffuser | Ø450x250        |
|     | DDR 060 025 065S 9040 10 99 OP 40 00     | 65        | 8640               | >80 | 4000    | 120° Diffuser | Ø650x250        |

[www.atellighting.com](http://www.atellighting.com)

# Dimple Drums End



Surface Mounted Surface Mounted Luminary

---

| SKU | Product Code                         | Power (W) | Luminous Flux (LM) | CRI | CCT (K) | Optics        | Dimensions (mm) |
|-----|--------------------------------------|-----------|--------------------|-----|---------|---------------|-----------------|
|     | END                                  | 65        | 8640               | >80 | 4000    | 120° Diffuser | Ø650x250        |
|     | DDR 090 025 145S 9040 10 99 OP 40 00 | 145       | 19575              | >80 | 4000    | 120° Diffuser | Ø910x250        |
|     | END                                  |           |                    |     |         |               |                 |