Voon

Pendant Pendant Luminary




Luminaire Group	Pendant
Mounting Type	Pendant
Luminary Color	RAL 9005 - RAL 9006 - RAL 9010
Housing	Dkp Sheet
Optics	Diffuser
Light Source	LED
Electrical Protection Class	CLASS II
IP	40
IK	02
Operating Temperature	-20°C / +40°C
Luminous Flux	2400 lm
Consumption Power	30 W
Luminaire Efficiency	80 lm/W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	2700K/3000K/4000K/6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Driver Brand	Tridonic
LED Brand	Samsung
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	>70.000 hours
Option	On-Off / Dali / 1-10V / With Emergency Kit

Technical Drawing



Photometric Curve



SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
19000357□	VON 115 020 030P 8030 10 99 OP 20 00	30	2400	>80	4000	120° Opal Diffuser	115x200x76,5