

Hoap Moss




Pendant Acoustic Solutions Luminary




Luminaire Group	Acoustic Solutions
Mounting Type	Pendant
Luminaire Color	RAL 9005 - RAL 9006 - RAL 9010
Housing	Aluminum Extrusion & Acoustic Panel
Optics	Opal Diffuser
Light Source	LED
Electrical Protection Class	CLASS II
IP	40
IK	02
Operating Temperature	-20°C / +40°C
Luminous Flux	6010 lm / 7730 lm / 9650 lm
Consumption Power	38 W / 52 W / 65 W
Luminaire Efficiency	158 lm/W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	2700K/3000K/4000K/6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Driver Brand	Tridonic
LED Brand	Samsung
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	>70.000 hours
Option	On-Off / Dali / 1-10V / With Emergency Kit

Technical Drawing



Photometric Curve



SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
15002761	HPM 060 010 038S 8040 10 99 OP 40 00	38	6010	>80	4000	120° Diffuser	Ø600x10
15002785	SRC 089 089 078P 8040 10 99 OP 40 00 F	52	7730	>80	4000	120° Diffuser	Ø900x10
15002809	HPM 120 010 065S 8040 10 99 OP 40 00	65	9650	>80	4000	120° Diffuser	Ø1200x10