


Pole Mounted Park & Garden Luminary





Luminaire Group	Park & Garden
Mounting Type	Pole Mounted
Luminary Color	RAL 9006 - RAL 9005 - RAL 9010
Housing	Aluminum Extrusion
Optics	12° 40° 90° Reflector
Light Source	LED
Electrical Protection Class	CLASS II
IP	66
IK	08
Operating Temperature	-20°C / +40°C
Luminous Flux	900 lm
Consumption Power	10 W
Luminaire Efficiency	90 lm/W
Color Rendering (CRI)	>80
Light Color Temperature (CCT)	2700K/3000K/4000K/6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Driver Brand	Tridonic
LED Brand	Samsung
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	>70.000 hours
Option	On-Off / Dali / 1-10V

Technical Drawing



Photometric Curve





SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
	OGN 010 010 010M 8040 10 12 LN 20 00	10	900	>80	4000	12° Reflektor	Ø100
		10	900	>80	4000		Ø100
	OGN 010 010 010M 8040 10 90 LN 20 00	10	900	>80	4000	90° Reflector	Ø100