

Promete M




Road Lighting & Floodlight Luminary




Luminaire Group	Road Lighting & Floodlight
Luminary Color	RAL 9005
Housing	Aluminum Injection Electrostatic Powder Coated
Optics	Symmetrical / Asymmetrical° Lens & Tempered Glass
Light Source	LED
Electrical Protection Class	CLASS II
IP	66
IK	08
Operating Temperature	-40°C / +55°C
Luminous Flux	15600 lm / 18200 lm / 19500 lm / 21600 lm / 24000 lm / 29000 lm
Consumption Power	120 W / 140 W / 150 W / 180 W / 200 W / 250 W
Luminaire Efficiency	120 lm/W
Color Rendering (CRI)	>70
Light Color Temperature (CCT)	3000K/4000K/6500K
Color Tolerance	< 3 SDCM
Driver Type	On/Off
Input Voltage / Frequency	220-240 V AC 50/60 Hz
Power Factor	>0.9
Surge	1kV
THD (AKIM)	>%20
LED life	>100.000 hours

Technical Drawing



Photometric Curve



www.atellighting.com

Promete M



Road Lighting & Floodlight Luminary

SKU	Product Code	Power (W)	Luminous Flux (LM)	CRI	CCT (K)	Optics	Dimensions (mm)
	PRO 042 038 120Y 8040 10 AS LN 66 00	120	15600	>70	4000	Asymmetric Lens	420x379x65
	PRO 042 038 140Y 8040 10 AS LN 66 00	140	18200	>70	4000	Asymmetric Lens	420x379x65
	PRO 042 038 150Y 8040 10 AS LN 66 00	150	19500	>70	4000	Asymmetric Lens	420x379x65
	PRO 042 038 180Y 8040 10 AS LN 66 00	180	21600	>70	4000	Asymmetric Lens	420x379x65
	PRO 042 038 200Y 8040 10 AS LN 66 00	200	24000	>70	4000	Asymmetric Lens	420x379x65
	PRO 042 038 250Y 8040 10 AS LN 66 00	250	29000	>70	4000	Asymmetric Lens	420x379x65
	PRO 042 038 120Y 8040 10 SM LN 66 00	120	15600	>70	4000	Symmetrical	420x379x65
	PRO 042 038 140Y 8040 10 SM LN 66 00	140	15600	>70	4000	Symmetrical	420x379x65
	PRO 042 038 150Y 8040 10 SM LN 66 00	150	19500	>70	4000	Symmetrical	420x379x65
	PRO 042 038 180Y 8040 10 SM LN 66 00	180	21600	>70	4000	Symmetrical	420x379x65
	PRO 042 038 200Y 8040 10 SM LN 66 00	200	24000	>70	4000	Symmetrical	420x379x65
	PRO 042 038 250Y 8040 10 SM LN 66 00	250	29000	>70	4000	Symmetrical	420x379x65